

What is claimed is:

1. A linear actuator, comprising:

a stator having a coil wound around an end portion  
5 of a rail-shaped magnetic substance; and

a mover which faces a rail-shaped portion of said  
stator, relatively moves along the rail-shaped portion,  
and includes a magnetic substance, wherein

an electric current flows through the coil to  
10 centrally produce magnetic flux on the rail-shaped  
portion facing said stator, thereby obtaining magnetic  
thrust of said mover.

2. A first component which is formed by rail-shaped  
15 magnetic pieces in substantially parallel rows, each  
of which has a coil wound around at an end portion of  
a longitudinal direction of the piece and makes a  
periodical magnetic change along the longitudinal  
direction of the piece by flowing an electric current  
20 through the coil; and

a second component facing said first component at  
predetermined spacing, and having N and S magnetic poles  
along the longitudinal direction of the plurality of  
pieces, wherein

25 said second component can be moved relative to

said first component along the longitudinal direction of said first component by differentiating distribution of magnetic changes of the plurality of pieces of said first components on a surface facing said second  
5 component.

3. A linear actuator, comprising:

a stator having K (K indicates and integer equal to or larger than 2) stator piece pairs, and each stator  
10 piece pair is composed of two stator pieces which are parallel-placed rail-shaped magnetic substances having a plurality of projections arranged at regular spacing T in a longitudinal direction, a bridge made by magnetic substance connecting one end of each stator piece  
15 together magnetically, and a coil wound around the bridge to magnetize the two stator pieces for opposite polarities; and

a mover having K mover piece pairs, and each mover piece pair is composed of magnetically-connected two  
20 mover pieces which are faced at predetermined spacing to said two stator pieces one to one which comprise said stator piece pair, and each mover piece has a magnetic core and magnetic poles formed on a portion of the magnetic core facing to said stator piece and arranged  
25 such that all or part of the N poles face to projections

of the stator piece when all or part of the S poles face to slots between the projections, wherein:

in each of K sets of one stator piece pair and one mover piece pair facing to each other,

5 two sets of a stator piece and a mover piece facing to each other are arranged such that positions of the magnetic poles on the mover piece to the projections on the stator piece in one set are shifted relative to those of the other set by  $T/2$  in the longitudinal  
10 direction of said stator;

with the K sets of one stator piece pair and one mover piece pair, the positions of the magnetic poles on the mover pieces to the projections on the stator pieces are sequentially shifted relative to each other  
15 at regular spacing along the longitudinal direction of said stator; and

thrust along the longitudinal direction of said stator can be produced on said mover by sequentially applying an electric current to a coil of each stator  
20 piece pair in a time series.

4. The linear actuator according to claim 3, wherein:

said stator piece pair is formed such that the projections of its two stator pieces face to each other;

25 and

said mover piece pair is provided between the two stator pieces in the stator piece pair corresponding to the mover piece pair.

5 5. A linear actuator, comprising:

a stator having M (M indicates an integer equal to or larger than 3) stator pieces, each of which is formed by a rail-shaped magnetic substance having a plurality of projections arranged at regular spacing  
10 in a longitudinal direction, and which are arranged parallel to each other, with one end of the stator pieces magnetically connected, and with a coil situated to each of the stator pieces to magnetize the projections; and

a mover having M mover pieces, which are faced at  
15 predetermined spacing to said stator pieces one to one, and each mover piece has a magnetic core, which is magnetically-connected to the cores of adjacent mover pieces, and magnetic poles formed on a portion of the magnetic core facing to said stator piece and arranged  
20 such that all or part of the N poles face to projections of the stator piece when all or part of the S poles face to slots between the projections, wherein:

with M sets of one stator piece and one mover piece facing to each other, the positions of the magnetic poles  
25 on the mover pieces to the projections on the stator

pieces are sequentially shifted relative to each other at regular spacing along the longitudinal direction of said stator; and

thrust along the longitudinal direction of said  
5 stator can be produced on said mover by sequentially applying an electric current to a coil of each stator piece in a time series.

6. The linear actuator according to claim 3, wherein  
10 said mover piece is configured by closely coupling a core of a strong magnetic substance with a permanent magnet as a magnetic pole.

7. The linear actuator according to claim 4, wherein  
15 said mover piece is configured by closely coupling a core of a strong magnetic substance with a permanent magnet as a magnetic pole.

8. The linear actuator according to claim 5, wherein  
20 said mover piece is configured by closely coupling a core of a strong magnetic substance with a permanent magnet as a magnetic pole.

9. The linear actuator according to claim 3, wherein  
25 said bridge to connect the stator pieces

magnetically and said coils are also provided at the other end of the stator.

10. The linear actuator according to claim 4, wherein  
5 said bridge to connect the stator pieces magnetically and said coils are also provided at the other end of the stator.

11. The linear actuator according to claim 5, wherein  
10 said bridge to connect the stator pieces magnetically and said coils are also provided at the other end of the stator.

12. The linear actuator according to claim 6, wherein  
15 said bridge to connect the stator pieces magnetically and said coils are also provided at the other end of the stator.

13. The linear actuator according to claim 3, wherein  
20 a sensor coil is wound in a slot between the projections of said stator pieces, and an absolute position of said mover can be detected based on a change of inductance of the sensor coil made when said mover passes over the sensor coil.

14. The linear actuator according to claim 4, wherein  
a sensor coil is wound in a slot between the  
projections of said stator pieces, and an absolute  
position of said mover can be detected based on a change  
5 of inductance of the sensor coil made when said mover  
passes over the sensor coil.

15. The linear actuator according to claim 5, wherein  
a sensor coil is wound in a slot between the  
10 projections of said stator pieces, and an absolute  
position of said mover can be detected based on a change  
of inductance of the sensor coil made when said mover  
passes over the sensor coil.

15 16. The linear actuator according to claim 6, wherein  
a sensor coil is wound in a slot between the  
projections of said stator pieces, and an absolute  
position of said mover can be detected based on a change  
of inductance of the sensor coil made when said mover  
20 passes over the sensor coil.

17. The linear actuator according to claim 9, wherein  
a sensor coil is wound in a slot between the  
projections of said stator pieces, and an absolute  
25 position of said mover can be detected based on a change

of inductance of the sensor coil made when said mover passes over the sensor coil.

18. The linear actuator according to claim 13, wherein  
5 said sensor coil is configured by a part of a coil for driving said mover wound around the bridge of said stator.

19. The linear actuator according to claim 14, wherein  
10 said sensor coil is configured by a part of a coil for driving said mover wound around the bridge of said stator.

20. The linear actuator according to claim 15, wherein  
15 said sensor coil is configured by a part of a coil for driving said mover wound around the bridge of said stator.

21. The linear actuator according to claim 16, wherein  
20 said sensor coil is configured by a part of a coil for driving said mover wound around the bridge of said stator.

22. The linear actuator according to claim 17, wherein  
25 said sensor coil is configured by a part of a coil



10000 壹萬圓  
 5000 伍仟圓  
 2000 貳仟圓  
 1000 壹仟圓  
 500 伍佰圓  
 200 貳佰圓  
 100 壹佰圓  
 50 伍拾圓  
 20 貳拾圓  
 10 壹拾圓  
 5 伍圓  
 2 貳圓  
 1 壹圓  
 0.5 伍角  
 0.2 貳角  
 0.1 壹角  
 0.05 伍分  
 0.02 貳分  
 0.01 壹分